

ULTRA LOW PROFILE MAG DRILL FROM STEELMAX®

D1 Low Profile

VERY LOW PROFILE ELECTRIC DRILL FOR RESTRICTED SPACE

The **D1 Low Profile** is an ultra-low-profile mag drill, that fits in the tightest of work spaces. It is a perfect solution for any applications in confined spaces, where typical mag drills are too large. A powerful motor and strong, electromagnetic base enable drilling of holes up to 1-7/16" (36 mm) diameter to a depth of up to 1-3/16" (30 mm).

The **D1 Low Profile** Mag Drill accepts both TCT and HSS cutters as well as twist drill bits with a standard 3/4" Weldon shank.



FEATURES

- Ultra low profile mag drill – only 7" tall – with electromagnetic base
- Light weight – only 21 lbs (9.5 kg)
- 1-7/16" (36 mm) diameter x 1-3/16" (30 mm) depth of cut maximums with annular cutters
- Accepts Weldon Shank twist drill bits up to 1/2" diameter
- Over 1-1/2" stroke (39 mm)
- Integrated swarf guard
- Convenient lifting handle for easy transportation

STANDARD SET INCLUDES:

- Drilling machine
- Plastic case
- Handle
- Handle adapter
- Pilot pin
- Safety strap
- 4 mm hex wrench
- Operator's Manual



The D1 Low Profile fits in the tightest spots



Annular Cutter:
max 1-7/16"
(36mm)



Twist drill:
max 1/2" (12mm)
with 3/4" Weldon
Shank



Depth of cut:
up to 1-3/16"
(30mm)



Stroke:
1-1/2"
(39mm)



Speed:
350 rpm



Motor Power:
920 W



Weight:
21 lbs
(9.5 kg)


Steelmax

The tools of innovation.

DI Low Profile Technical Specification

Motor Speed (under load)	350 rpm (115V); 370 rpm (230 V)
Motor Power	920 W
Weight	21 lbs (9.5 kg)
Maximum Hole Size - Annular Cutter	1 7/16" (36 mm)
Maximum Hole Size - Twist Bit	1/2" (12 mm)
Max countersinking	Ø 1 9/16" (40 mm)
Stroke	1-1/2" (39 mm)
Max depth of cut	1-3/16" (30mm) with TCT cutters 13/16" (20mm) with HSS cutters *
Voltage	110-120 V, 50-60 Hz 220-240 V, 50-60 Hz
Power consumption	1000 W
MFSC	Yes
Magnetic clamping force	2,000 lbs (8900 N)
Magnet Base Dimensions	3-9/16 x 7-1/16 x 1-1/2" (90 x 180 x 38.5 mm)
Min. Workpiece Thickness	1/4" (6mm)
Tool holder	3/4" Weldon Shank

* Up to 1" (25 mm) when used with an optional long quill assembly (SM-ZSP-0521-04-00-00)




Optional Accessories:

- SM-ZSP-0521-04-00-00-0
Long quill assembly
- SM-PJM-000003
Coolant bottle with nozzle



Hole making with various tools:



Compact design for height restricted areas. Detachable feed lever can be fixed from either side



Max milling capacity up to 1-7/16" (36mm)



Easily work out of position



Lifting handle for easy transportation



Handy plastic case

Steelmax

The tools of innovation.

For ordering and customer service, or to request detailed product information or demonstration videos, contact:

877-833-5629

STEELMAX.COM

sales@Steelmax.com

Fax: 303-690-9172

