

## D2x PORTABLE MAGNETIC DRILL

### PURPOSE-DESIGNED PRODUCTION DRILLING MACHINE

The **D2x** magnetic drill from Steelmax is a powerful drilling machine for every-day industrial use. With its high-torque, 1260-watt electric motor, the **D2x** is capable of drilling 2" (51 mm) diameter holes in material up to 3" (76 mm) thick. The **D2x** features a revolutionary – and service-friendly – design with a unique, semi-automatic, self-adjusting gib system that requires minimal maintenance over the drill's life and produces accurate hole cutting. A proprietary replaceable spline on the end of the armature shaft further reduces maintenance and repair costs.

The **D2x** accepts arbors and drill chucks with Morse Taper No. 2 shafts and easily switches between drilling with annular cutters and solid twist drill bits for maximum flexibility.

Equipped with an electromagnetic Energy Saving Base (ESB), the **D2x** uses only 50% of the power when the motor is not under load, which dramatically increases the operating life of the electromagnet. A Magnetic Field Shape Control (MFSC) system provides maximum holding power on thin material.

A Magnetic Power Adhesion Control (MPAC) module detects an adequate adhesive force of electromagnetic base for safe operation.

#### FEATURES

- 2" (51 mm) diameter x 2" (51 mm) depth of cut
- Unique self-adjusting gib system extends cutter life
- Through-spindle coolant system with integrated reservoir
- Safe magnet™ circuitry recognizes magnetic holding power
- Powerful 1260W motor and all metal housing make the D2x a production tool for industrial environments
- 2-speed gearbox works with twist bits to 7/8" and annular cutters to 2" diameter
- Integrated gearbox housing with slide
- Adjustable cutter guard with built-in chip breaker
- Semi-automatic gib backlash adjustment
- Energy Saving Base (ESB)
- Magnetic Power Adhesion Control (MPAC)
- Magnetic Field Shape Control (MFSC)



**Steelmax**

The tools of innovation.



<b>D2x Technical Specifications</b>		
Spindle	MT2	
Tool holder	3/4" (19 mm) Weldon	
Milling cutter (Core drill) Ø	max 2" (51 mm)	
Twist drill Ø	max 7/8" (23 mm)	
Countersinking Ø	max 2" (51 mm)	
Stroke	6" (153 mm)	
Max depth of cut	3" (76 mm)	
Voltage	115V/60Hz or 230V/50Hz	
Power consumption [W]	1300	
Motor power	1260 W 1.7 HP	
Speeds [rpm]	200 400	
MFSC (Magnetic Field Shape Control)	yes	
Magnet – on 1" (25 mm) plate	Dead lift	Drill point breakaway
	2697 lbs (1223 kg)	1074 lbs (487 kg)
Magnet base dimensions	3-9/16" x 7-1/16" x 1-7/8" (90 x 180 x 48 mm)	
ESB (Energy Saving Base)	yes	
MPAC (Magnetic Power Adhesion Control)	yes	
Minimum workpiece thickness	5/16" (8 mm)	
Semi-automatic gib backlash adjustment	yes	
Weight	35 lbs 5 oz (16.5 kg)	
Part number	<b>SM-D2x</b> (115V/60Hz) <b>SM-D2x-230</b> (230V/50Hz)	

**Standard shipping set:**

- Magnetic base drilling machine
- Metal shipping box
- MT2 Arbor with 3/4" (19 mm) Weldon Bore – with cooling ring
- Swarf shield/Cutter guard
- Coolant bottle assembly
- Safety chain
- Set of tools with wedge
- Instruction manual
- Standard shipping weight – 60 lbs

**Optional Accessories:**

**SM-DC-MT2-13** Morse Taper #2, 1/2" drill chuck



For ordering and customer service, or to request detailed product information or demonstration videos, contact:

877-833-5629

STEELMAX.COM

sales@Steelmax.com

Fax: 303-690-9172